



**PRECISION TESTING LABORATORIES, INC.**  
313 Hill Avenue, Nashville TN 37210  
Phone 615-254-3401 Fax 615-254-3488  
www.precisiontesting.com

**Laboratory Report No. 53791**  
10-Apr-23

Page 1 of 1

Mr. Oscar Murillo  
Lucas del Norte S.A.  
24 Calle 20-56  
Zona 12 Guatemala  
HFR5+MW Guatemala City, Guatemala

Cc: Ms. Corina Castellanos

**PO#:** n/a

**Item:** Three (3) pair of footwear

**Identification:** Style: COLECCION RHINO SUELA PU PATRIOT 2.0 PUNTERA COMPOSITE  
Size: 9 US  
Gender: Men's


**Purpose:** Impact Resistance, Compression Resistance, Electric Hazard Resistance; ASTM F 2412-18a/ASTM F 2413-18

Test	Unit of Measure	Specimen Results			Average	Requirements	Pass / Fail
<b><u>Impact Resistance</u></b>							
<b><u>ASTM F 2412-18a</u></b>						Male	
<b><u>ASTM F 2413-18</u></b>							
	Resistance, in.	0.327	0.289	0.231	0.282	0.500 min.	Fail
	Velocity, in./sec	118.5	118.5	118.5	118.5	117.9±2.4"sec.	Pass
<b><u>Compression Resistance</u></b>							
<b><u>ASTM F 2412-18a</u></b>							
<b><u>ASTM F 2413-18</u></b>							
	Resistance, in.	0.774	0.783	0.828	0.795	0.500 min.	Fail
<b><u>Electric Hazard Resistance</u></b>							
<b><u>18kv for 1 minute</u></b>							
<b><u>ASTM F 2412-18a</u></b>							
<b><u>ASTM F 2413-18</u></b>							
	Begin, mA.	0.09	0.09	0.07	0.08	1.0 mA max.	Pass
	End, mA.	0.10	0.12	0.09	0.10	1.0 mA max.	Pass

Test Note: The test specimens were conditioned and tested in accordance with ASTM F2412-18a Standard Conditions of 22°C (± 2°C) and 50% RH (± 5%).

This report is limited to and related only to the particular instrument, material or other subject to which it refers. These test results can not be compared to results obtained using different methods or under different conditions. No representation is made that similar articles will be of like quality. Neither Precision Testing Laboratories, Inc. (hereinafter "Precision Testing") nor their officers, directors, managers or employees, shall be responsible for any loss or damage resulting directly or indirectly from any failure, error or omission in testing, or in the reporting of test results. Precision Testing has no controls, and assumes no responsibility for the tested product's functionality or use. Precision Testing's liability shall not exceed the fees paid for the testing reflected on this report. Precision Testing observes and maintains client confidentiality, and limits reproduction of this report, except in full, without prior approval of Precision Testing.

tj

Signed:   
Eric Olson, President